



Rack

Passive Products

Fiber Products

Out Door Wall Mount Data Sheet

www.dds-eg.com



The DDS Outdoor Wall Mount Cabinet is a 19" wall-mounted network enclosure made from cold-rolled steel (SPCC) with a powder-coated RAL 7035 finish.

It is rated IP 65 and holds up to 100 kg of static load.

It has a lockable door, bottom cable entry points and fan-ready ventilation.

It protects and organizes network, CCTV and control equipment in indoor and semi-outdoor environments.

It comes in 4U to 15U sizes, with 450 mm and 600 mm depth options.



Heavy-duty steel body

Electrostatic powder-coated finish for durability and corrosion resistance.



Standard 19" rails

For switches, patch panels, routers and control devices.



Fan-ready ventilation

Internal design supports optional fan installation.



Lockable front door

Solid door that keeps your equipment secure.



Bottom cable entry

Neat and efficient cable management.



IP 65 protection

Built for indoor and semi-outdoor use.



Technical Specifications

Mounting dimensions	19"
Cabinet type	Wall mount
Static load	100 kg
Material thickness	Mounting rails: 2.00 mm others: 1.50 mm
IP protection class	IP 65
Color	RAL 7035
Structure	Assembled, welded construction
Material	Steel Plate Cold Rolled Commercial (SPCC)

Models & Dimensions

645 Series | 600 W × 450 D

Model	Rack units	Width (mm)	Depth (mm)	Height (mm)
DNC-04U645OD	4U	600	450	370
DNC-06U645OD	6U	600	450	470
DNC-09U645OD	9U	600	450	600
DNC-12U645OD	12U	600	450	750
DNC-15U645OD	15U	600	450	870

660 Series | 600 W × 600 D

Model	Rack units	Width (mm)	Depth (mm)	Height (mm)
DNC-04U660OD	4U	600	600	370
DNC-06U660OD	6U	600	600	470
DNC-09U660OD	9U	600	600	600
DNC-12U660OD	12U	600	600	750
DNC-15U660OD	15U	600	600	870